



TRANSTECH™ IV+

Inline and Dipstick Automatic Transmission Fluid Exchange System

The TransTech IV+ combines both Inline and Dipstick capabilities allowing for the two most common methods of ATF exchange from a single machine. With both Inline and Dipstick services together in one cabinet, the TransTech IV+ occupies reduced floor space with minimal investment while providing service to a wider variety of vehicles.

Inline Exchange

This conventional ATF exchange method provides an effective transmission flush by connecting directly to the transmission cooler lines. New fluid flows through the transmission as old fluid is directed into the TransTech IV+ waste tank in a 1-to-1 ratio.

Dipstick Exchange - The TransTech IV+ features a convenient Dipstick option that allows an effective ATF exchange through the transmission dipstick tube. This useful alternative is suitable when cooler lines are corroded or difficult to access.

- **Automatic Inline Exchange** - Connect to a transmission cooler line and press one button—walk away until the service is complete
- **Dipstick Exchange** - A convenient dipstick tube exchange requiring no tools or adapters
- **Drain Pan Feature** - Allows operator to drain transmission pan for a convenient and mess-free filter change
- **Transmission Cooler Flush Feature** - Allows operator to flush transmission cooler and cooler lines

- **Patented Level Synchronization** - Ensures the transmission cannot be under or overfilled
- **Automatic Bypass** - Ensures that transmission will not run out of fluid during the exchange process
- **26 Quart New Fluid Reservoir** - Allows user to service large capacity transmissions
- **High Volume Pump** - For rapid and efficient service

500-1125B

Model	TransTech™ IV+
Input	12 VDC 8A

Machine Dimensions

Height	99 cm (39")
Width	53.3 cm (21")
Depth	43 cm (17")

Carton Dimensions

Height	104 cm (41")
Width	61 cm (24")
Depth	48 cm (19")
Shipping Weight	40.8 kg (90 lbs)

New Fluid Capacity	24.6 L (26 qt)
Waste Tank Capacity	24.6 L (26 qt)

Length of Power Cord	3 m (10 ft)
Length of Hose	3 m (10 ft)

Warranty	One Year
----------	----------



Adapters

Scan the QR code to view a listing of all adapters.

FOR USE WITH TRANSTECH™ IV+



MOTORVAC® UNIVERSAL ATF PROTECTANT

By using MotorVac Universal ATF Protectant, a full service facility can service virtually all vehicles by stocking only synthetic DEXRON® III and DEXRON® VI.

- Eliminates the need to stock multiple ATF types
- Prolongs transmission life by reducing excessive heat and friction
- Ensures smoother shifting and eliminates transmission shudder
- Conditions and restores seals and O-rings to help eliminate leaks

400-1030AS



MOTORVAC® TRANSTECH™ TT2K

2-Step Cleaning and Conditioning Kit

- Add the service chemical in through the dipstick

STEP 1 TT1 ATF Cleaner:

Removes varnish, sludge and contaminants that build up in the transmission.

STEP 2 TT2 ATF Conditioner:

Rejuvenates seals and reduces the possibility of leaks. The conditioner also reduces oxidation and heat-related breakdowns.

400-0137



1300 30 40 60 - www.efi.com.au